

CODE ALERT®

Emergency & Nurse Call Solutions



CodeWatch

The CodeWatch® transmitter is a discreet, small and lightweight transmitter that is worn on the wrist or ankle of a resident and has a 6 month to 1 year life expectancy.

Dimensions (LxWxD)

2" x 1.5" x 0.5"

Weight

1 oz

Color / Composition

Off-white with printed color centers, thermoplastic co-polyester

Frequency

66 kHz or 262 kHz

Battery Life Expectancy

262 kHz - 1 year, Lithium Ion
66 kHz - 6 month, Lithium Ion

Operating Temperature

32-104°F

Water Resistance

Rated to IP-67 for use in the shower

Compliance

FCC Part 15b compliant
Conforms to UL 294 standards

RFT Part Number(s)

9000-0144 (CodeWatch Transmitter (CWTX), Flag Design, 70/100, 66 kHz)
9000-0145 (CodeWatch Transmitter (CWTX), Flag Design, 70/100, 262kHz)
9000-0146 (CodeWatch Transmitter (CWTX), Flag Design, 80/100, 66 kHz, ID)
9000-0147 (CodeWatch Transmitter (CWTX), Flag Design, 80/100, 262 kHz, ID)
9000-0148 (CodeWatch Transmitter (CWTX), Flower Design, 70/100, 66 kHz)
9000-0149 (CodeWatch Transmitter (CWTX), Flower Design, 70/100, 262 kHz)
9000-0150 (CodeWatch Transmitter (CWTX), Flower Design, 80/100, 66 kHz, ID)
9000-0151 (CodeWatch Transmitter (CWTX), Flower Design, 80/100, 262 kHz, ID)
9000-0138 (CodeWatch Transmitter (CWTX), 70/100, 66 kHz)
9000-0139 (CodeWatch Transmitter (CWTX), 70/100, 262 kHz)
9000-0140 (CodeWatch Transmitter (CWTX), 80/100, 66 kHz, ID)
9000-0141 (CodeWatch Transmitter (CWTX), 80/100, 262 kHz, ID)

Transmitters and Banding

CodeWatch® (watch like appearance) and standard transmitters are used with the CODE ALERT® Wander Management solution to reduce risk of resident elopments. If a resident wearing a transmitter gets close to a monitored exit, a near-door antenna will recognize the transmitter and depending on configuration, can sound an alarm, lock the door, and/or notify staff members.

262 kHz Options



* actual size

66 kHz Options



CODE ALERT®

Emergency & Nurse Call Solutions

Adult

The Adult transmitter is a lightweight and compact transmitter that is worn on the ankle or wrist of a resident.

Dimensions (LxWxD)	1.6" x 2" x 0.7"
Weight	1.28 oz
Color / Composition	Off-white, polycarbonate
Frequency	66 kHz or 262 kHz
Battery Life Expectancy	Available in 1, 1.5, 2, and 3 year models
Operating Temperature	32-104°F
Water Resistance	Rated to IP-67 for use in the shower
Compliance	FCC Part 15b compliant Conforms to UL 294 standards
RFT Part Number(s)	9000-0436 (TX 9120/80, 1-year, 66 kHz, ID) 9000-0437 (TX 9120/80, 1-year, 262 kHz, ID) 9000-0432 (TX 9120/70, 1.5-year, 66 kHz) 9000-0434 (TX 9120/70, 1.5-year, 262 kHz) 9000-0414 (Standard Transmitter (TX) 9120/80, 2-year, 66 kHz, ID) 9000-0424 (Standard Transmitter (TX) 9120/80, 2-year, 262 kHz, ID) 9000-0413 (Standard Transmitter (TX) 9120/70, 3-year, 66 kHz) 9000-0423 (Standard Transmitter (TX) 9120/70, 3-year, 262 kHz) 9000-1000 (Transmitter Tester)



* actual size

Banding

All banding is latex free, tamper-resistant, and designed for one-time use.



PVC
Band

Dimensions (LxW)	16" x .08"
Color / Composition	Blue, nylon webbing Gray, blue or green, flexible PVC plastic
Fitting	0.75" adjust setting holes; 2 sets of nickel-coated brass snaps
RFT Part Number(s)	3000-0213K (Blue Bands, Nylon, 10 Pack) 3000-0217K (Gray Bands, PVC, 10 Pack) 3000-0241K (Blue Bands, PVC, 10 Pack) 3000-0238K (Green Bands, PVC, 10 Pack)



Nylon
Band

